

## Technical data:

No.	Type	Size (w×l×h) mm	Assembly dimensions (w×l×h) mm	Ground plate mm	Installing through...	Weight kg
1	LS 550 for 1 photoelectric barrier	80x 100x 550	75x 80x160	160x140	Removable, lockable front panel	2.5
2	LS 1100 for 2 photoelectric barriers	80x 100x1,100	75x 80x160	160x140	Removable, lockable front panel	4.7
3	ST 1100 for key switch, magnetic card reader	80x 100x1,100	75x 80x160	160x140	Removable, lockable front panel	4.7
3a	ST 1850 for 2 key switches or 2 magnetic card readers	80x 100x1,850	top: 75x 80x160 bottom: 75x 80x160	180x200	Removable, lockable front panel	7.0
4	CK 1100 for code switches or card readers	145x145x1,100	125x130x160	220x220	Removable, lockable front panel	7.0
5	PKW 1100 for access control systems, intercom systems	350x300x1,100	330x250x195	Internal mounting, incl. template	Lockable lateral access panel, hinged hood	20.0
6	PKW 1220 for access control systems, intercom systems	400x450x1,220	490x400x265	Internal mounting, incl. template	Lockable lateral access panel, hinged hood	28.5
7	BUS 1850 for access control systems, intercom systems	350x300x1,850	330x250x195	Internal mounting, incl. template	Lockable lateral access panel, hinged hood	28.0
8	PKW / LKW 2250 for access control systems, intercom systems	350x300x2,250	top: 330x250x195 bottom: 340x220x220	Internal mounting, incl. template	Lockable lateral access panel, hinged hood	30.5

Colours: Hoods, blue (RAL 5012), bottom part, white (RAL 9010) – RAL custom colours optional against surcharge

We reserve the right to make technical alterations.

Your partner for distribution – installation – service:

# ELKA pillars and housings made of aluminium



# ELKA pillars and housings made of aluminium

